

Fiber Management

DOME ENCLOSURE

DER013

PRODUCT SPECIFICATIONS

Model DER013 Dome Enclosure provides protection over direct, branch and terminal connection for cables. They are easy and reliable to install, delivering high mechanical strength against every environmental condition. Widely used in many applications.

APPLICATIONS

- Aerial
- Direct-Burial
- Wall & Pipeline Mounting



FEATURES

BENEFITS

HQ Polypropylene	Sturdy IP 68 & IK 10
Up to 360F	No Special Tools Required
Adjustable Cassettes	Protects Fibres in Field

ENVIRONMENTAL SPECIFICATIONS

Operation (°C)	-40~+65
Installation (°C)	-40~+65

SPECIFICATIONS

Purpose	Aerial, Direct-Burial, Wall & Pipeline Mounting
Capacity	360
Cable Entries	17
Dimensions (mm)	450 x 230
Weight (kg)	7.5-8.0
Sealing	Heat shrink
Material	Polypropylene
Splicing Per Cassette	12,24
Cable Diameter (mm)	φ08~25.0



ORDERING INFORMATION

Model	Seal	Cable Entries	Core Size/Capacity
DER013	Mechanical	17	12,24,36,48,60,72,84,96,108, 120,132,144,156,168,180,192, 204,216,228,240,252,264,276,288 312.336,360

For any queries, please contact Technoline Solutions team using the details below.