

## Fiber Management

# DOME ENCLOSURE

# DER14

### PRODUCT SPECIFICATIONS

Model DER14 Dome Enclosure provides protection over direct, branch and terminal connection for cables. They are easy and reliable to install, delivering high mechanical strength against every environmental condition. Widely used in many applications.

### APPLICATIONS

- Aerial
- Direct- Burial
- Wall & Terrace Mounting

### FEATURES

HQ Polypropylene  
Up to 144F  
Adjustable Cassettes

### BENEFITS

Sturdy IP 68 & IK 10  
No Special Tools Required  
Protects Fibres in Field

### SPECIFICATIONS

Purpose	Aerial, Direct-Burial, Wall & Pipeline Mounting
Capacity	144
Cable Entries	20
Dimensions (mm)	526xφ235
Weight (kg)	4.5-5.0
Sealing	Heat Shrink
Material	Polypropylene
Splicing Per Cassette	6 or 12
Cable Diameter (mm)	φ8~20.0

### ORDERING INFORMATION

Model	Seal	Cable Entries	Core Size/Capacity
DER014	Heat Shrink	20	6,12,24,36,48,60,72,84,96,108,120,132,144

For any queries, please contact Technoline Solutions team using the details below.



### ENVIRONMENTAL SPECIFICATIONS

Operation (°C)	-40~+65
Installation (°C)	-40~+65

