

Fiber Management

DOME ENCLOSURE

DER016

PRODUCT SPECIFICATIONS

Model DER16 Dome Enclosure provides protection over direct, branch and terminal connection for cables. They are easy and reliable to install, delivering high mechanical strength against every environmental condition. Widely used in many applications.

APPLICATIONS

- Aerial
- Direct- Burial
- Wall & Terrace Mounting



FEATURES

BENEFITS

HQ Polypropylene	Sturdy IP 68 & IK 10
Up to 48F	No Special Tools Required
Adjustable Cassettes	Protects Fibres in Field

ENVIRONMENTAL SPECIFICATIONS

Operation (°C)	-40~+65
Installation (°C)	-40~+65

SPECIFICATIONS

Purpose	Aerial, Direct-Burial, Wall & Pipeline Mounting
Capacity	48
Cable Entries	4
Dimensions (mm)	288x178mm
Weight (kg)	1.8-1.9
Sealing	Heat Shrink
Material	Polypropylene
Splicing Per Cassette	12
Cable Diameter (mm)	φ16



ORDERING INFORMATION

Model	Seal	Cable Entries	Core Size/Capacity
DER016	Heat Shrink	4	12,24,36,48

For any queries, please contact Technoline Solutions team using the details below.