

Fiber Management

DOME ENCLOSURE

DER02

PRODUCT SPECIFICATIONS

Model DER02 Dome Enclosure provides protection over direct, branch and terminal connection for cables. They are easy and reliable to install, delivering high mechanical strength against every environmental condition. Widely used in many applications.

APPLICATIONS

- Aerial
- Direct-Burial
- Wall & Terrace Mounting



FEATURES

HQ Polypropylene
Up to 96F
Adjustable Cassettes

BENEFITS

Sturdy IP 68 & IK 10
No Special Tools Required
Protects Fibres in Field

SPECIFICATIONS

Purpose	Aerial, Direct-Burial, Wall & Pipeline Mounting
Capacity	96
Cable Entries	19
Dimensions (mm)	380x245x130
Weight (kg)	4.5-5.0
Sealing	Mechanical
Material	Polypropylene
Splicing Per Cassette	12,24
Cable Diameter (mm)	φ8~17.5

ENVIRONMENTAL SPECIFICATIONS

Operation (°C)	-40~+65
Installation (°C)	-40~+65

ORDERING INFORMATION

Model	Seal	Cable Entries	Core Size/Capacity
DER02	Mechanical	19	12,24,36,48,60,72,84,96



For any queries, please contact Technoline Solutions team using the details below.