

Fiber Management

DOME ENCLOSURE

DER03

PRODUCT SPECIFICATIONS

model DER03 Dome Enclosure provides protection over direct, branch and terminal connection for cables. They are easy and reliable to install, delivering high mechanical strength against every environmental condition. Widely used in many applications.

APPLICATIONS

- Aerial
- Direct- Burial
- Wall & Terrace Mounting



FEATURES

BENEFITS

HQ Polypropylene	Sturdy IP 68 & IK 10
Up to 96F	No Special Tools Required
Adjustable Cassettes	Protects Fibres in Field

SPECIFICATIONS

Purpose	Aerial, Direct-Burial, Wall & Pipeline Mounting
Capacity	96
Cable Entries	9
Dimensions (mm)	470 x 210
Weight (kg)	2.0
Sealing	Heat shrink
Material	Polypropylene
Splicing Per Cassette	12,24
Cable Diameter (mm)	φ8~20

ENVIRONMENTAL SPECIFICATIONS

Operation (°C)	-40~+65
Installation (°C)	-40~+65



ORDERING INFORMATION

Model	Seal	Cable Entries	Core Size/Capacity
DER03	Heat shrink	9	12,24,36,48,60,72,84,96

For any queries, please contact Technoline Solutions team using the details below.