

## Fiber Management

# DOME ENCLOSURE

# DER05

### PRODUCT SPECIFICATIONS

model DER05 Dome Enclosure provides protection over direct, branch and terminal connection for cables. They are easy and reliable to install, delivering high mechanical strength against every environmental condition. Widely used in many applications.

### APPLICATIONS

- Aerial
- Direct- Burial
- Wall & Terrace Mounting



FEATURES	BENEFITS
HQ Polypropylene	Sturdy IP 68 & IK 10
Up to 144F	No Special Tools Required
Adjustable Cassettes	Protects Fibres in Field

SPECIFICATIONS	
Purpose	Aerial, Direct-Burial, Wall & Pipeline Mounting
Capacity	144
Cable Entries	5
Dimensions (mm)	450x230
Weight (kg)	3.8-4.2
Sealing	Heat Shrink
Material	Modified Polymer Plastic
Splicing Per Cassette	12,24
Cable Diameter (mm)	φ8~17.5

### ENVIRONMENTAL SPECIFICATIONS

Operation (°C)	-40~+65
Installation (°C)	-40~+65



### ORDERING INFORMATION

Model	Seal	Cable Entries	Core Size/Capacity
DER05	Heat Shrink	5	12,24,36,48,60,72,84,96,108,120,132,144

For any queries, please contact Technoline Solutions team using the details below.