

Fiber Management

DOME ENCLOSURE

DER06

PRODUCT SPECIFICATIONS

Model DER06 Dome Enclosure provides protection over direct, branch and terminal connection for cables. They are easy and reliable to install, delivering high mechanical strength against every environmental condition. Widely used in many applications.

APPLICATIONS

- Aerial
- Direct-Burial
- Wall & Terrace Mounting

FEATURES

HQ Polypropylene
Up to 288F
Adjustable Cassettes

BENEFITS

Sturdy IP 68 & IK 10
No Special Tools Required
Protects Fibres in Field

SPECIFICATIONS

Purpose	Aerial, Direct-Burial, Wall & Pipeline Mounting
Capacity	288
Cable Entries	7
Dimensions (mm)	528x258
Weight (kg)	5.0-5.5
Sealing	Heat Shrink
Material	Polypropylene
Splicing Per Cassette	12,24
Cable Diameter (mm)	φ8~20

ORDERING INFORMATION

Model	Seal	Cable Entries	Core Size/Capacity
DER06	Heat Shrink	7	12,24,36,48,60,72,84,96,108,120,132,144,156,168,180,192,204,216,228,240,252,264,276,288



ENVIRONMENTAL SPECIFICATIONS

Operation (°C)	-40~+65
Installation (°C)	-40~+65



For any queries, please contact Technoline Solutions team using the details below.