

Fiber Management

DOME ENCLOSURE

DER08

PRODUCT SPECIFICATIONS

Model DER08 Dome Enclosure provides protection over direct, branch and terminal connection for cables. They are easy and reliable to install, delivering high mechanical strength against every environmental condition. Widely used in many applications.

APPLICATIONS

- Aerial
- Direct- Burial
- Wall & Terrace Mounting

FEATURES

HQ Polypropylene
Up to 120F
Adjustable Cassettes

BENEFITS

Sturdy IP 68 & IK 10
No Special Tools Required
Protects Fibres in Field

SPECIFICATIONS

Purpose	Aerial, Direct-Burial, Wall & Pipeline Mounting
Capacity	120
Cable Entries	5
Dimensions (mm)	470x210
Weight (kg)	4.3-4.8
Sealing	Mechanical
Material	Polypropylene
Splicing Per Cassette	24
Cable Diameter (mm)	φ08~17.5

ORDERING INFORMATION

Model	Seal	Cable Entries	Core Size/Capacity
DER08	Mechanical	5	12,24,36,48,60,72,84,96,108,120



ENVIRONMENTAL SPECIFICATIONS

Operation (°C)	-40~+65
Installation (°C)	-40~+65



For any queries, please contact Technoline Solutions team using the details below.